

SO-5000SE

Ophthalmic Microscope

- Sturdy floor stand mounted.
- Foot controlled focus and zoom.
- High resolution Olympus optics.
- High intensity coaxial LED light
 - remove the cost and inconvenience of spare bulbs for the life of the microscope.
- Operate from mains power (with internal regulation for voltage fluctuations) or 12V battery.
- Includes coaxial streaming video & assistant microscope
- Options
 - aluminium transit case for microscope.
 - PD Adjuster



SPECIFICATIONS

OPTICAL HEAD

Viewing System	Trinocular stereoscopic, convergent angle 10° for viewing comfort. Image erection by high resolution prism system.
Eyepieces	Tube inclination 45° High field number 22 for wide field of view High eye relief 24.6mm and reversible eye cups for ease of use by spectacle wearers.
Magnification	Zoom, 4.2x to 25x continuous.
Field of View	53mm to 9mm depending on magnification.
Refractive Error Correction	±5D anisometropia
Pupillary Distance	50mm to 76mm, eyepiece tubes locked for ease of adjustment.
Focusing	Fine focus range ±25mm.
Mould Protection	Anti-fungus pellets (three year protection) standard.

COAXIAL VIDEO

Complete with beam splitter, C-mount adaptor, video camera, large screen LCD monitor and monitor mounting arm, cables, power supply.

ILLUMINATION

Type	Coaxial, direct optical delivery system.
Lamp	20W LED, 75,000 lux, lifetime of the microscope.
UV and Blue light hazard	UV and blue light hazard: Filtered to 435nm
Colour Temperature	4,100°K

MOUNTING SYSTEM

Arm	Elbow and angle-poise movement in horizontal and vertical directions. Variable friction locks.
Head Tilt	+5° to -45°
Vertical Tension	Adjustable gas spring to set lifting force.
Materials	Specially selected to resist rust and corrosion.
Dimensions	Vertical pillar to head optical axis, Max. 930mm (37")

POWER SUPPLY

Mains Input	100-240VAC, 50-60Hz, 2.0A max. @ 100VAC
Mains Output Regulation	< ±5%
Protection	Over voltage, over current and short circuit protection
Battery / Auxiliary Input	12V DC, polarity and current surge protected.
Approvals	Medical grade approvals CSA C22.2 No. 60601.1-M90 UL 60601-1, 2nd edition IEC 60601-1 CE marked EN 60601-1-2:2001

PACKAGING

Microscope excluding floor stand	Dimensions of carton: 81 x 52 x 31cm Weight in carton: 25kg
Floor stand (two cartons)	Dimension of each carton: 90 x 27 x 29 cm Weight in each carton: 22kg
Monitor	Dimensions of carton: 45 x 25 x 35cm Weight of carton: 6 kg

OPTIONS

PD Adjuster (SO-1510)	PD Adjuster
Aluminium Transit Case (SO-5000A)	The aluminium transit case is available for the microscope. The floor stand and monitor are only shipped in cartons.

Scan Optics
32 Stirling Street Thebarton SA
5031 Adelaide Australia

Tel: +61 (8) 8234 9120
Fax: +61 (8) 8234 9417
Email: admin@scanoptics.com.au
Web site: www.scanoptics.com.au



Quality Endorsed Company
Certified to ISO 9001

Lic. No. QEC 10722